



Self-Service Checkout Kiosk

The Focus of Retail Innovation

Saving time in checkout queues Reducing labor costs Creating more customer experiences



A board module of applications for supermarket, hyper, grocery store, ticket, restaurant, food, court, etc. There are 2 kinds of style for wall-mounted and free standing in commercial environment. 23.8-inch full HD touch display, fast and accurate scanning of product barcode, payment QR code. 3D face recognition camera, credit payment and other demands could be customizated.



Free-standing display



Wall-mounted display



Operating System

Android7.1 WIN7/WIN10



CPU

Andriod-RK3288 WIN-Intel Core i3



HD Display

Capacitive touch screen supports 10-point touch



Storage

Android-2GB /eMMC8GB WIN-4GB /SSD 64G



Printer

80mm thermal printer



Supports barcode

Supports barcode and QR code, mobile phone screen and paper code



Speaker

5W Stereo



Wi-Fi

RJ45 2.4G Wi-Fi



Power Input

AC110-220V



Credit Payment

Optional



0

	Specificatoin of Self-Service Checkout Kiosk				
No.	Components	Brand / Model	Main Specifications		
1	Android System	Android	Provided by customer		
2	Display+Touch screen	23.8"	Screen Size	23.8inch	
			Pixel Number	1920*1080	
			Pixel pitch	350cd/m²	
			Contrast	3000:1	
			Display Colors	16.7M	
			Viewing Angle	89°/89°/89°	
			LED Life Time	Min. 30000hrs	
			Touch point number	10 point"	
			Input mode	Finger or capacitor pen	
			Surface hardness	≥6H	
3	Receipt Printer	PT80KM-XA	Receipt Printer Method	Thermal printing	
			Print width	80mm	
			Speed	250mm/sec(Max)	
			Resolution	203dpi	
			Print length	100KM	
			Autocutter	included	
4	QR code scaner	XZG004	Image (Pixels)	640 pixels(H) x 480 pixel(V)	
			Light Source	LED	
			Field of View	68°(H) x 51° (V)	
			Minimum Resolution:	5 mil	
			1-D	"Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, Matrix 2 of 5, Code 11, Industrial 2 of 5, Standard 2 of 5, Plessey, MSI-Plessey, etc"	
			2-D	PDF417, QR Code, DataMatrix, etc	
5	Camera (Optional)	"HIKVISION E14a"	Photosensitive element	CMOS camera	
			Camera pixel	4 million	
			Resolution	2K	
			Focusing mode	Autofocus	
			Interface	USB2.0	
6	Power Supply	LRS-150-12	AC input voltage range	110-220VAC	
			DC output voltage	12V	
7	Speaker	HZ	Dual channel amplified speak	kers for Stereo , 8Ω 5W.	
8	KIOSK Cabinet		Dimention	decided when finish production	
			Color	Optional by customer	
		1. The material of outer metal cabinet is durable 1.5mm thickness cold-roll steel frame; 2. The design is elegant and easy to install and operate; Moistureproof,Antirust, Anti-acid, Anti-dust,Static free; 3.Color and LOGO are upon customers' requests.			
9	Accessories	Security Lock for anti theft , tray for easy maintenance,2 ventilation fans, Wire-Lan Port; Power sockets for electricity, USB ports;Cables, Screws, etc.			
10	PC	i3 6100cpu +8+128G			

